


6 CUBIC FT. RUBBER BELT AIR BLAST MACHINE

Model # 6RB-A

FEATURES

- 800 LB CAPACITY
- 6 BLAST NOZZLES
- 460VAC, 3 PHASE
- CONTINUOUS MOLDED RUBBER BELT
- SAFETY INTERLOCKS
- REVERSING MILL
- AUTOMATIC TIMER CONTROLS
- 1 YEAR MACHINE WARRANTY
- SMALL OPERATING FOOTPRINT
- OPTIONAL DUST COLLECTOR



TECHNOLOGY. SERVICE. SOLUTIONS.

Phone: 877.355.7577 • Fax: 262.785.1066 • 6682 W Greenfield Ave, Suite 103 • West Allis, WI 53214 • www.bct-us.com



BLAST CLEANING TECHNOLOGIES



TECHNICAL DATA

6 CUBIC FT. AIR BLAST MACHINE

Model # 6RB-A

AIR BLAST SYSTEM

Air Blast Nozzles: Six (6) 3/8" diameter replaceable venturi style carbide nozzles
Height adjustable for optimal blast coverage
External compressed air supply required
Automated nozzle movement for even parts coverage

CABINET CONSTRUCTION

Cabinet: Formed 1/4" steel with access panels for easy belt replacement. Service doors in back to inspect and clean abrasive screen
Door: Pneumatically operated reinforced rubber door
Work Load Height: 46"
Work Load Capacity: 37" wide x 27.5" diameter, 6 cubic feet or 800 lbs. maximum capacity
Conveyor: Continuous molded rubber belt, four ply construction, integrated direct molded tumble ridges
Conveyor Roller: Solid shaft rollers supported by ball bearings
Conveyor Speed: 10 feet per minute

POWER AND AIR REQUIREMENTS

Electric Supply: 460 VAC, 3 Phase, 60 Hz. Others available by request
Controls: NEMA 12 rated electrical enclosure, 24VDC controls, IEC motor starters, pushbutton controls, hour meter, abrasive blast and post blast timers
Electric Motors: Totally enclosed, fan cooled (TEFC)
Belt Drive: 1/2HP, 1800 RPM
Air Requirement: 100-120CFM @ 60/80 PSI 3/4" NPT furnished for air connection

SEPARATOR SYSTEM

Abrasive Screening: Tramp metal and trash screen in cabinet. Access doors for cleaning and inspection
Abrasive Separator: 600 CFM centrifugal for optimum sizing of contaminate removal (integrated, standard)
Abrasive Required: 50 pounds for initial start-up
Optional Dust Collector: 600 CFM centrifugal style

SAFETY AND STRUCTURE

Safety: Blast nozzle and work door interlock. Drive chain fully guarded
Shipping Weight: 4000 pounds
Machine Dimensions: 5'-5" Width x 5'-5" Length x 12'-4" Height

TECHNOLOGY. SERVICE. SOLUTIONS.

Phone: 877.355.7577 · Fax: 262.785.1066 · 6682 W Greenfield Ave, Suite 103 · West Allis, WI 53214 · www.bct-us.com